

MITSUBISHI FUSO
CANTER

FE73



*Original vehicle may differ from the displayed picture.

FUSO

FE73C SPECIFICATIONS (DRIVE SYSTEM: 4x2)

Mitsubishi Canter FE73

MODEL		
Model	Cab type	WIDE
	R.H.D.	FE73CE6R
Crew		3
DIMENSIONS mm		
Wheelbase		3,350
Overall length		6,040
Overall width		1,865
Overall height, approx.		2,105
Tread	front	1,390
	rear	1,435
Ground clearance, approx.		200
Loadspan		4,555
Frame width		700
Front overhang		1,015
Rear overhang		1,675
WEIGHTS kg		
Kerb weight *1		2,005
Max. G.V.W.		5,700
CALCULATED PERFORMANCE		
Max. speed	km/h (mph)	112
Max. gradeability	(tan θ) %	48
Min. turning radius	m (ft)	6.6
ENGINE		
Model		MITSUBISHI FUSO 4D33-7A
Type		4 stroke-cycle, water-cooled direct injection diesel engine
No. of cylinders		Bosch type 4 plungers in line
Piston displacement		4.214 L
Max. output *2		87kW at 3,000rpm (JIS Gross)
Max. torque		304 N.m at 1,600rpm (26.6 r/s) (JIS Gross)
Air cleaner		Dry paper element
Alternator		24 Volt, 50 Amp.
DRIVE LINE		
Clutch		C4W30 Hydraulic control, diaphragm spring, single dry plate
Transmission		M035S5
	gear ratios	5 forward and 1 reverse speed, 2nd to 5th synchromesh, 1st and rev. constantmesh gears
Final reduction gear		D033H
	ratio	Single reduction, hypoid gear
CHASSIS		
Frame		Parallel, tapered channel section with reinforcement & crossmembers rolled high tensile steel
Steering		Ball nut type, Integral type hydraulic power booster. Telescopic and tilt steering column with steering lock, Power Steering
Suspension		Semi-elliptic, laminated leaf springs
Shock absorbers		Hydraulic double acting telescopic type on front and rear axles
Axle	front	F200T, Reverse Elliot, "I" beam
	rear	R033T, Full floating type
Brake	service	Hydraulic with vacuum servo assistance, dual circuit
	parking	Internal expanding type on propeller shaft at rear of transmission
	exhaust	Vaccum operated, butterfly valve type
Tire	front	Signle, 7.00R16
	rear	Dual, 7.00R16
Fuel tank capacity		100 lit.
Meter Cluster		• Speedometer (km/h) with odometer and trip meter • Fuel gauge • Water temp. gauge
Warning lamps and indicators		• Turn signal/hazard • Vacuum pressure • Brake fluid level/parking brake • High beam/passing • Exhaust brake • Oil pressure
CAB		
Construction		Tilt type with torsion bar, all steel welded construction
Driver's seat		High back type 16 stage reclining, 19 stage sliding